

IN THE CLAIMS

Please amend the claims as follows. Added text is underlined and deleted text is either struck through or shown in double enclosing brackets. Applicants aver that no new matter has been added.

1. (Currently Amended) A method of producing a video signal from a system used for outputting video programming to at least one viewer, said method comprising:
 - receiving a first video signal at said system, the first video signal representing a first video feed;
 - processing said first video signal to produce a first image stored in memory of said system, said first image not intended to be displayed independently;
 - receiving a second video signal at said system, the second video signal representing a second video feed different from the first video feed;
 - processing said second video signal to produce a second image stored in said memory of said system, said second image not intended to be displayed independently;
 - receiving a presentation description in said system, said presentation description comprising a set of instructions that define a plurality of manners ~~manner~~ in which a portion of said first image and a portion of said second image are to ~~may~~ be combined, ~~the~~ selecting a manner from the plurality of manners in which the portion of said first image and the portion of the second image ~~images~~ are to be combined ~~being selected from a plurality of different manners of image combinations~~ based upon user preference information stored in said system, ~~and the presentation description instructions also defining a sequence of operations performed over time;~~
 - combining said portion of said first image with said portion of second image in accordance with said selected manner ~~in which the images are combined~~ of said ~~presentation description~~ to produce a combined image; and
 - outputting said combined image as said video signal as part of said video programming to said at least one viewer.

2. (Previously Presented) The method as set forth in claim 1 wherein said combining further comprises:

applying a mask that defines said portion of said first image.

3. (Previously Presented) The method as set forth in claim 1 wherein said combining further comprises:

generating a logical combination of said portion of said first image and said portion of said second image.

4. (Previously Presented) The method as set forth in claim 1 wherein said combining further comprises:

generating a mathematical combination of said portion of said first image and said portion of said second image.

5. (Previously Presented) The method as set forth in claim 1 wherein said combining further comprises:

scaling said portion of said first image.

6. (Previously Presented) The method as set forth in claim 1 wherein said combining further comprises:

warping said portion of said first image.

7. (Previously Presented) The method as set forth in claim 1 wherein said accessing said presentation description further comprises:

fetching said presentation description across a network.

8. (Previously Presented) The method as set forth in claim 1 wherein said accessing said presentation description further comprises:

receiving a network address at which said presentation description can be accessed;
fetching said presentation description from said network address.

9. (Previously Presented) The method as set forth in claim 1 wherein said accessing said presentation description further comprises:

selecting said presentation description from a plurality of presentation descriptions contained in said first video signal.

10. (Previously Presented) The method as set forth in claim 1, said method further comprising:

modifying said presentation description in response to input from said at least one viewer.

11. (Previously Presented) The method as set forth in claim 1, said method further comprising:

processing said first video signal to produce first audio data stored in said memory of said system;

processing said second video signal to produce second audio data stored in said memory of said system;

accessing said presentation description that describes the manner in which said first audio data and said second audio data are combined; and

combining said first audio data and said second audio data in accordance with said presentation description.

12. (Currently Amended) A method of producing a sequence of combined images in a system used for outputting video programming to said at least one viewer, said method comprising:
- receiving a first video signal at said system;
 - processing said first video signal to produce a first sequence of images stored in memory of said system, said first sequence of images not intended to be displayed independently;
 - receiving a second video signal at said system;
 - processing said second video signal to produce a second sequence of images stored in said memory of said system, said second sequence of images not intended to be displayed independently;
 - receiving a plurality of presentation descriptions in said system, the plurality of presentation descriptions each comprising a set of instructions that define a manner in which a portion of said first sequence of images and a portion of said second sequence of images are to ~~may~~ be combined, and the plurality of presentation descriptions each including an identifier;
 - selecting one of the plurality of presentation descriptions based upon a selected identifier corresponding to user preference information stored in the system, the selected presentation description defining the manner in which the sequences of images are to be combined, ~~and the selected presentation description instructions also defining a sequence of operations performed over time;~~
 - combining said portion of said first sequence of images with said portion of said second sequence of images in accordance with the selected presentation description to produce a finalized sequence of combined images; and
 - outputting said finalized sequence of combined images as a part of said video programming to said at least one viewer.
13. (Previously Presented) The method as set forth in claim 12 wherein said combining further comprises:
- applying a mask specified in the selected presentation description that defines said portion of said first sequence of images.

14. (Previously Presented) The method as set forth in claim 13 wherein said applying a mask further comprises:

executing program code that modifies said mask to select a different portion of at least one image of said first sequence of images.

15. (Previously Presented) The method as set forth in claim 12 wherein said combining further comprises:

generating a mathematical combination of said portion of one image of said first sequence of images and said portion of one image of said second sequence of images.

16. (Previously Presented) The method as set forth in claim 12 wherein said combining said video signals further comprises:

generating a logical combination of said portion of one image of said first sequence of images and said portion of one image of said second sequence of images.

17. (Previously Presented) The method as set forth in claim 12 wherein said combining said video signals further comprises:

scaling said portion of one image of said first sequence of images.

18. (Previously Presented) The method as set forth in claim 12 wherein the selected identifier being based also on demographics of the viewer.

19. (Previously Presented) The method as set forth in claim 12, said method further comprising:

modifying the selected presentation description in response to input from said at least one viewer.

20. (Currently Amended) A method of controlling generation of a combined video signal for use as video programming to at least one viewer in a system at said at least one viewer's premises from a broadcast site, said method comprising:

transmitting a first digital video signal to said system, said first digital video signal comprising a first image not intended to be displayed independently, the first digital video signal representing a first video feed;

transmitting a second digital video signal to said system substantially simultaneously with said first digital video signal, said second digital video signal comprising a second image not intended to be displayed independently, the second digital video signal representing a second video feed, and the second video feed being different from the first video feed;

loading image combination code into said system; and

transmitting a presentation description to said system, said presentation description comprising a set of instructions that define a plurality of manners ~~manner~~ in which a portion of said first image contained in said first digital video signal are to ~~may~~ be combined with a portion of said second image contained in said second digital video signal to produce said combined video signal for use as video programming to at least one viewer, ~~the a manner from the plurality of manners~~ in which the portion of said first image and the portion of said second image ~~images~~ are combined to be being ~~selected from a plurality of different manners of combinations~~ based upon user preference information stored in said system, ~~and the presentation description instructions also defining a sequence of operations performed over time.~~

21. (Previously Presented) The method as set forth in claim 20 wherein said providing a presentation description further comprises:

transmitting a network address that said system employs to access said presentation description.

22. (Previously Presented) The method as set forth in claim 20 wherein said providing a presentation description further comprises:

transmitting said presentation description to said system as a part of said first digital video signal.

23. (Previously Presented) The method as set forth in claim 20 wherein said providing a presentation description further comprises:

selecting said presentation description from a plurality of presentation descriptions wherein said presentation description conforms to the requirements of said system.

24. (Previously Presented) The method as set forth in claim 20 wherein said providing a presentation description further comprises:

altering a general presentation description to conform to the requirements of said system.

25. (Previously Presented) The method as set forth in claim 20 wherein said providing a presentation description further comprises:

tailoring a general presentation description to correspond to a viewer preference.

26. (Previously Presented) The method as set forth in claim 20 wherein said providing a presentation description further comprises:

transmitting a plurality of presentation descriptions to said system from which said system selects one presentation description that conforms to the requirements of said system.

27. (Currently Amended) A system that produces a combined video signal for use as video programming to at least one viewer, said system comprising:

a processor;

a memory, said memory coupled to said processor;

a tuner/decoder that receives a first video signal, representing a first video feed, and a second video signal, representing a second video feed different from the first video feed, substantially simultaneously and that routes control information contained in said first video signal to said processor and that routes first video data from said first video signal and second video data from said second video signal to a video decoder; said video decoder that decodes said first video data and produces a first video image in said memory and that decodes said second video data and produces a second video image in said memory, said first video image and said second video image not intended to be displayed independently;

a video controller, said video controller receiving a presentation description, said presentation description comprising a set of instructions that define a plurality of manners ~~manner~~ in which a portion of said first video image are to ~~may~~ be combined with a portion of said second video image to produce said combined video signal, ~~the~~ a manner from the plurality of manners in which the portion of said first video image and the portion of said second video image ~~images~~ are to be combined ~~being selected from a plurality of different manners of combinations being selected~~ based upon user preference information stored in said system ~~and the presentation description instructions also defining a sequence of operations performed over time;~~

program code operating in said processor that employs said presentation description and that accesses said portion of said first video image and said portion of said second video image in said memory and that combines said portion of said first video image and said portion of said second video image according to the selected manner of combination to create said combined video signal; and

a video output unit that outputs said combined video signal to a display device as a part said video programming to said at least one viewer

28. (Previously Presented) The system as set forth in claim 27, said system further comprising:
a network interface that accesses a remote server to receive said presentation description.
29. (Previously Presented) The system as set forth in claim 27 wherein said decoder further produces first audio data in said memory from said first video information and produces second audio data in said memory from said second video information.
30. (Previously Presented) The system as set forth in claim 29 wherein said presentation description further specifies the manner in which said first audio data is combined with said second audio data.
31. (Previously Presented) The system as set forth in claim 27, said system further comprising:
a user interface that receives an input from said at least one viewer that modifies said presentation description.
32. (Canceled)
33. (Previously Presented) The system as set forth in claim 27 wherein said program code operating in said processor further comprises:
a software routine that controls said decoder to perform at least part of the combination of said portion of said first video image and said portion of said second video image in a manner specified by said presentation description.
34. (Previously Presented) The system as set forth in claim 27 wherein said program code operating in said processor further comprises:
a software routine that selects said presentation from a plurality of presentation descriptions contained in said first video signal.

35. (Canceled)

36. (New) The method of claim 1, wherein the presentation description further comprises dynamic variables that control one or more of a display movement, gradually changing perspective, and a display varying process that provides image modification that corresponds to changes in a scene to which the combined image is applied.

37. (New) The method of claim 1, wherein the presentation description specifies the portion of the first image and the portion of the second image to be combined.

38. (New) The method of claim 1, wherein the presentation description specifies scene locations at which the portion of the first image and the portion of the second image are to be combined.

39. (New) The method of claim 1, wherein the selected manner comprises one or more of a pixel by pixel replacement of the portion of the first image by the portion of the second image, a deforming of one of the portion of the first image or the portion of the second image, overlaying and ghosting of the portion of the first image with the portion of the second image, and a color key replacement of the portion of the first image with the portion of the second image.